



PRODUCT SPECIFICATIONS DOMO Champion Ascari 4G/M

Applications	Soccer, Indoor soccer, Multisport
Fibre	Polyethylene Monofilament straight / Diamond Plus / 360 μ m thickness / 13.500 dtex Multi directional curled (MDC) monofilament / 160 μ m thickness / 7.000 dtex
Production Method	Linear Tufting
Gauge	3/8"
# stitches / lm	180 / lm
# tufts / m ²	18.900 / m ²
# piles / m ²	529.200 / m ²
Pile Height	30 mm
Pile Weight	2.850 gr / m ²
Total Height	32 mm
Total Weight	4.350 gr / m ²
Tuft Cloth	Polypropylene, UV-Stabilized, with incorporated glass fibre fabric reinforcement, 300 gr / m ²
Backing	Latex, 1.200 gr / m ²
Infill (*)	Ca. 15 kg/m ² silica sand
Shock pad	See laboratory test report
Roll Width	400 cm
Roll Length	As per lay-out
Colour	Green
Colour Lines	White (straight yarn= white; curled yarn = same as the green colour)
Colour Fastness	Scale 7 (DIN 54004)
UV-Stability	> 5.000 hours UV-A
Water Permeability	> 6.10 ⁻⁴ m / s
Pile Anchorage	> 30 N

(*) Non-filled products can be more sensitive to the build-up of static electricity.

Sports and Leisure Group NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data (max.10%). Sports and Leisure Group NV guarantees the technical quality of the proposed article.



A POWERFUL EXPERIENCE